







IR & Thermocouple INFRARED THERMOMETER

- 3 Sec. Fast Thermocouple Response time (optional)
- HACCP Zone Display (TCT303 Series)
- IP Classification: IP65(TCT303 Series)/ IP54(TCT23 Series)
- Bright White LED as pointer (TCT303 Series)
- 2 in 1 design: Infrared + Foldable Thermocouple Probe
- °C/°F Switch Mode & Auto Power Off



<p>HACCP Check (TCT3 Series)</p>  <p>↓4°C / ↓40°F 4-60°C / 40-140°F ↑60°C / ↑140°F</p>	<p>Dual LCD</p> 	<p>3 Sec. Fast Measurement (optional)</p> 	<p>Infrared Measurement</p> 	<p>Thermocouple Measurement</p> 	<p>TCT103 Blue Panel Label</p> 
---	---	---	--	---	--

	TCT303	TCT303F	TCT23N	TCT103	TCT103F
Description			IRT + Probe		
IP Classification	IP65		IP54		
Meas. Range	Infrared	-55~250°C(-67~482°F)		-33~220°C(-27~428°F)	
	Thermocouple	-55~330°C(-67~626°F)		-55~330°C(-67~626°F)	
Infrared Accuracy (Tamb=23±3°C)	±2% of reading or 2°C(4°F) whichever is greater	-33~0°C: ±(1°C+0.1/°C)°C 0~65°C: ±1°C 65~250°C: ±1.5% of reading		±2% of reading or 2°C(4°F) which is greater	
Thermocouple Accuracy	±1% of reading or 0.8°C(1.5°F) whichever is greater (Tamb=23±6°C)	below -5°C: ±1°C, -5~65°C: ±0.5°C, above 65°C: ±1% of reading (Tamb=23±3°C)		±1% of reading or 0.8°C(1.5°F) whichever is greater (Tamb=23±6°C)	
Distance: Spot	2.5:1			1:1	
Emissivity Range	0.95 default, adjustable from 0.1 to 1 step .01				
Resolution	0.2°C/0.5°F at -9.9~199.9(°C/°F), otherwise 1°C/1°F		0.1°C/0.1°F at -9.9~199.9(°C/°F), otherwise 1°C/1°F		
Mode	Max / Min, Lock, HACCP Check			Max / Min, Lock	
Power Supply	AAA x 2		CR2450 x 1		CR2032 x 1

Specifications are subject to change without notice