




IP54 INFRARED THERMOMETER

- Laser sight / Dual beam laser technology
- Real time maximum temperature reading
- Recall the last reading
- Large LCD Screen, with bright amber color Backlight
- IP54 Splash Proof Classification



	TN43SL1(Y)/TN43PL1(Y)	TN43SL2(Y)/TN43PL2(Y)
Description	IRT + Laser	
Measurement Range	-50~460°C(-58~860°F)	-60~550°C(-76~1022°F)
Full Range Accuracy (Tamb=23±3°C)	≥0°C: ±2.5% of reading or 2.5°C(4.5°F) whichever is greater <0°C: ±(2.5°C+0.05/°C)°C	≥0°C: ±2% of reading or 2°C(4°F) whichever is greater <0°C: ±(2°C+0.05/°C)°C
Distance:Spot	12:1	
Emissivity Range	0.95 or 0.70(The default emissivity is 0.95)	0.95 default adjustable 0.1 to 1 step .01
Resolution	0.2°C/0.5°F at -9.9~199.9(°C/°F), otherwise 1°C/1°F	0.1°C/0.1°F at -76~999.9(°C/°F), otherwise 1°C/1°F
Mode	Real Time Max, Lock	Ave, Dif, Hi/Low Alarm, Real Time Max / Min, Lock
Power Supply	AAA x2	

Specifications are subject to change without notice